福建青拓上克不锈钢有限公司

Fujian Tsingtuo Shangke Stainless Co.Ltd.

产品质量证明书（EN10204 3.1）

PRODUCT QUALITY CERTIFICATE(EN10204 3.1)

地址(Add)：福建省宁德市福安市湾坞镇上洋村199号
No.199, Shangyang Village, Wanwu Town,
Fu'anCity,Ningde Province ,Fujian
电话(tel)：0593-6298199
传真(fax)：0593-6298199
邮编：355006

品名：不锈钢冷轧钢板和钢带 No. Cold rolled stainless steel plate, sheet and strip							客户名称 Customer	佛山市甬金新材料有限公司		证明书号： Certificate No	SKPZ20250100327
钢种 Type	SUS430B		表面 Surface	2B	标　准： Specification		JIS G 4305-2021			检验日期： Date of survey	2025/1/21

序号 No.	炉号 Heat Number	用途 Use	钢卷编号 Coil No.	规格 Size(mm)	重量 Weight (kg)	等级 Grade	化学成分（熔炼分析）Chemical composition（Heat analysis） %						拉伸试验 Tensile			硬度 Hardness (HV)	交货状态 State
							C	Si	Mn	P	S	Cr	抗拉强度T.S (N/mm2)	屈服强度Y.S (N/mm2)	伸长率 Elong (%)		
							0.00-0.12	0.00-0.75	0.00-1.00	0.00-0.04	0.00-0.03	16.00-18.00	≥420	≥205	≥22	≤200	
1	A241216AA17	430B-2B	SK241203400873-02	0.38*1255*C	8234	合格	0.027	0.276	0.340	0.023	0.0012	16.120	540	328	25	149	固溶处理 Soluttion
2	A241216AA17	430B-2B	SK241203400873-03	0.38*1255*C	6599	合格	0.027	0.276	0.340	0.023	0.0012	16.120	540	328	25	149	固溶处理 Soluttion
3	A241216AA17	430B-2B	SK241203400873-04	0.38*1255*C	6681	合格	0.027	0.276	0.340	0.023	0.0012	16.120	540	328	25	149	固溶处理 Soluttion
4	A241216AA18	430B-2B	SK241203400874-02	0.60*1258*C	7246	合格	0.024	0.303	0.330	0.024	0.0022	16.220	521	307	27	150	固溶处理 Soluttion
5	A241216AA18	430B-2B	SK241203400874-03	0.60*1258*C	7281	合格	0.024	0.303	0.330	0.024	0.0022	16.220	521	307	27	150	固溶处理 Soluttion
6	A241216AA18	430B-2B	SK241203400874-04	0.60*1258*C	7091	合格	0.024	0.303	0.330	0.024	0.0022	16.220	521	307	27	150	固溶处理 Soluttion
7	A241216AA18	430B-2B	SK241203400876-02	0.60*1262*C	7065	合格	0.024	0.303	0.330	0.024	0.0022	16.220	532	312	28	150	固溶处理 Soluttion
8	A241216AA18	430B-2B	SK241203400876-03	0.60*1262*C	7208	合格	0.024	0.303	0.330	0.024	0.0022	16.220	532	312	28	150	固溶处理 Soluttion
9	A241216AA18	430B-2B	SK241203400876-04	0.60*1262*C	7193	合格	0.024	0.303	0.330	0.024	0.0022	16.220	532	312	28	150	固溶处理 Soluttion
10	A241216AB16	430B-2B	SK241203400878-02	0.38*1255*C	7033	合格	0.020	0.315	0.330	0.026	0.0042	16.110	549	326	27	150	固溶处理 Soluttion
11	A241216AB16	430B-2B	SK241203400878-03	0.38*1255*C	6829	合格	0.020	0.315	0.330	0.026	0.0042	16.110	549	326	27	150	固溶处理 Soluttion
12	A241216AB16	430B-2B	SK241203400878-04	0.38*1255*C	7407	合格	0.020	0.315	0.330	0.026	0.0042	16.110	549	326	27	150	固溶处理 Soluttion
总计 Total					85867												

注释

1.拉伸实验原始标距为：50mm。
Tensile Test original gauge length ：50mm.
2.兹证明本表所列产品，均依标准规定制造、取样、试验和检验，并符合标准及合同要求。
We hereby certify that the products listed in this table are manufactured, sampled, tested and tested in accordance with the standards, and are in conformity with the standards and contract requirements.
3.本证明书需盖质量管理部专用章或经授权的销售部公章生效，复印无效。
This certificate is valid with the seal of the quality management department or the official seal of the authorized sales department, and the copy is invalid.
4.材料制造厂批准证书: PED 4.3（2014/68/EU） 证书编号：HPiVS-iP1001-192-Q-03-00;
Certificates of approval of manufacturer of materials: PED 4.3（2014/68/EU） No.：HPiVS-iP1001-192-Q-03-00
5.原产地：中国
COUNTRY OF ORIGIN: CHINA

品质部门印章
Quality Department